



Bent Axis Motors DIN Connection



Tank
Truck



Suction
Truck



Fire
Truck



Boat
Winch

* Intermittent operation refers to a max of 6 seconds per minute, representing e.g. peaks in rotational speed during unloading and acceleration.

	12	17	25	35	40	47	56	64	84	108	130
Displacement cm ³ /rev	12,5	17,1	25,5	34,3	41,1	47,2	56,1	63,5	83,7	108,0	130,1
Max Continuous rpm	2400	2400	2400	2400	2000	2000	2000	2000	1600	1600	1600
Max Intermittent rpm	3000	3000	3000	3000	2500	2500	2500	2500	2000	2000	2000
Max Continuous Bar	350	350	350	350	350	350	350	350	350	350	350
Max Intermittent Bar	400	400	400	400	400	400	400	400	400	400	400
Max Continuous Kw	14	19	29	39	46	52	62	70	74	96	99
Max Intermittent Kw	18	24	36	49	57	65	78	88	93	120	124
Starting Torque Theoretical Value Nm/bar	0,20	0,27	0,40	0,54	0,66	0,75	0,89	1,0	1,33	1,71	2,06
Weight Kg	9,0	9,0	9,0	9,0	14,0	14,0	14,0	14,0	19,0	19,0	19,0

		12	17	25	35	40	47	56	64	84	108	130
Connection Cover	S1									W	W	W
	S2					W	W	W	W			
	S3	W	W	W	W							
	V1									W	W	W
	V2			W	W	W	W	W	W	W	W	W
	R1					W	W	W	W	W	W	W
	K3	W	W	W	W							

