



Solenoid
Valves



	Code	Product Type	Air Inlet	Air Outlet	Max. Pressure Bar	Min. Pressure Bar	Temperature	Nominal Voltage	Nominal Current	Current Type	Weight (kg)
1	6S112V	Single	G1/4"	G1/4"	10	6	- 40~+80	12 Volt	650 mA	Direct Current	0,5
	6S124V	Single	G1/4"	G1/4"	10	6	- 40~+80	24 Volt	650 mA	Direct Current	0,5
2	6S212V	Double	G1/4"	G1/4"	10	6	- 40~+80	12 Volt	650 mA	Direct Current	1
	6S224V	Double	G1/4"	G1/4"	10	6	- 40~+80	24 Volt	650 mA	Direct Current	1
3	6S312V	Triple	G1/4"	G1/4"	10	6	- 40~+80	12 Volt	650 mA	Direct Current	1,5
	6S324V	Triple	G1/4"	G1/4"	10	6	- 40~+80	24 Volt	650 mA	Direct Current	1,5
4	6S412V	Quartet	G1/4"	G1/4"	10	6	- 40~+80	12 Volt	650 mA	Direct Current	2
	6S424V	Quartet	G1/4"	G1/4"	10	6	- 40~+80	24 Volt	650 mA	Direct Current	2